

IN THE CLAIMS

Please cancel claims 15, 16, and 37 and amend claims 2, 20, and 38-43 as indicated below.

1. (Previously Presented) A method for routing messages comprising:
receiving a message from a sender;
converting the message into an internal format, wherein said converting
comprises adding at least an attribute part to a data part of the received
message;
writing into said attribute part data extracted from said received message and data
indicative of a protocol by which the message was received; and
routing said converted message in dependence on the data in said attribute part.
2. (Currently Amended) The method of claim 1, comprising identifying ~~the~~ a format
in which the message was received, and writing data identifying that format into said
attribute part.
3. (Original) The method of claim 1, comprising determining where to send the
message in dependence on the attributes.
4. (Original) The method of claim 1, comprising authenticating the identity of the
sender of the message.
5. (Original) The method of claim 1, comprising identifying a set of services to
which the message is addressed.
6. (Original) The method of claim 4, comprising determining whether the sender is
authorised to access at least one service; and, in dependence on the result of said
authorisation determination, sending the converted message to the identified service.

7. (Original) The method of claim 6, in which said identified service updates the data held in the attribute part of the message.
8. (Original) The method of claim 6, comprising storing a plurality of routing rules and in which determining whether the sender is authorised to access at least one service comprises comparing said plurality of routing rules with the attributes of a converted message.
9. (Original) The method of claim 1, wherein said received message comprises a digital signature, the method comprising verifying the signature.
10. (Original) The method of claim 9, comprising writing into said attribute part data identifying the received digital signature.
11. (Original) The method of claim 1, comprising storing a plurality of routing rules; comparing the attributes of a converted message with the routing rules; and routing said converted message in dependence on said comparison.
12. (Previously Presented) The method of claim 1, further comprising:
determining whether there exists a transaction identifier associated with the
received message, the message corresponding to a transaction; and
generating a transaction identifier for the message in response to determining no
transaction identifier associated with the message exists.
13. (Previously Presented) The method of claim 12, further comprising:
utilizing a transaction identifier associated with the message to determine whether
there exists a previously stored context which indicates a state of the
transaction; and
creating a context associated with the message in response to determining no
context exists for the message.

14. (Previously Presented) The method of claim 13, wherein the transaction comprises a series of messages, and wherein the method further comprises updating a context associated with the transaction as the series of messages are processed.

15-16. (Cancelled).

17. (Previously Presented) A computer-readable medium encoded with computer-readable program code for configuring a computer system to route a message, the program code operable to:

receive a message from a sender;

convert the message into an internal format, wherein converting the message into an internal format comprises adding at least an attribute part to a data part of the received message;

write into said attribute part data extracted from said received message and data

indicative of a protocol by which the message was received; and

route said converted message in dependence on the data in said attribute part.

18. (Previously Presented) A computer-readable medium encoded with computer-readable program code translatable to configure a computer system to route a message, the program code operable to:

receive a message from a sender;

convert the message into an internal format, wherein converting the message into an internal format comprises adding at least an attribute part to a data part of the received message;

write into said attribute part data extracted from said received message and data

indicative of a protocol by which the message was received; and

route said converted message in dependence on the data in said attribute part.

19. (Previously Presented) A computer system for routing messages to one or more services comprising:

a parser for converting a message received from a sender into an internal format, wherein said converting comprises adding an attribute part to a data part of the received message, said attribute part containing data extracted from the received message and data indicative of a protocol by which the message was received; and
a router for routing the converted message in dependence on the data in said attribute part.

20. (Currently Amended) The computer system of claim 19, in which said parser is configured to identify ~~the~~a format in which the message was received, and to write data identifying that format into said attribute part.

21. (Original) The computer system of claim 19, in which said router is configured to determine where to send the message in dependence on the attributes.

22. (Original) The computer system of claim 19, in which said the router is configured to authenticate the identity of the sender of the message.

23. (Original) The computer system of claim 19, in which said router is configured to identify a set of services to which the message is addressed.

24. (Original) The computer system of claim 19, in which said router is configured to:
identify at least one service to which the message should be sent;
determine whether the sender is authorised to access said identified service; and,
in dependence on the result of said authorisation determination, selectively send the converted message to the identified service.

25. (Original) The computer system of claim 19, said router being configured to store a plurality of routing rules and to determine whether the sender is authorised to access a service by applying said rules to the attributes of a converted message.

26. (Original) The computer system of claim 19, wherein said parser is configured to verify signatures included in said received messages.

27. (Original) The computer system of claim 19, said parser comprising a plurality of applications for converting said received message, said parser selecting at least one of said applications in dependence on the data extracted from said received message.

28. (Original) The computer system of claim 27, wherein said data extracted from said received message includes a message type, said parser selecting at least one of said applications in dependence on the type of a message.

29. (Previously Presented) The computer system of claim 27, wherein said data extracted from said received message includes protocol data, and said parser selects at least one of said applications in dependence on the protocol(s) under which the message was received.

30. (Previously Presented) The computer system of claim 19, wherein the parser is further configured to: determine whether there exists a transaction identifier associated with the received message, the message corresponding to a transaction; and
generate a transaction identifier for the message in response to determining no transaction identifier associated with the message exists.

31. (Previously Presented) The computer system of claim 30, wherein the parser is further configured to:
utilize a transaction identifier associated with the message to determine whether there exists a previously stored context which indicates a state of the transaction; and
create a context associated with the message in response to determining no context exists for the message.

32. (Previously Presented) The computer system of claim 31, wherein the transaction comprises a series of messages, and wherein the method further comprises updating a context associated with the transaction as the series of messages are processed.

33. (Previously Presented) The computer system of claim 19, further comprising a plurality of protocol handlers each configured to extract protocol data from a message received in a particular format.

34. (Previously Presented) The computer system of claim 33, configured to select a protocol handler for extracting data from a received message, in dependence on the format in which the message is received.

35. (Previously Presented) The computer system of claim 33 configured to select a protocol handler in dependence on the type of data in the received message.

36. (Previously Presented) The computer system of claim 35, in which said protocol handler extracts message level protocol data and writes this into the attribute part of the converted message.

37. (Cancelled).

38. (Currently Amended) The computer readable medium program of claim ~~37~~17, ~~comprising computer-executable instructions for~~ further encoded with computer-readable code for configuring a computer system to ~~identifying the a~~ format in which the message was received, and ~~writing~~ write data identifying that format into said attribute part.

39. (Currently Amended) The computer readable medium program of claim ~~37~~17, ~~comprising computer-executable instructions for~~ further encoded with computer-readable code for configuring a computer system to ~~determining~~ determine where to send the message in dependence on the attributes.

40. (Currently Amended) The computer readable medium program of claim 3717, ~~comprising computer executable instructions for~~ further encoded with computer-readable code for configuring a computer system to authenticating ~~authenticate~~ the identity of the sender of the message.

41. (Currently Amended) The computer readable medium program of claim 3717, ~~comprising computer executable instructions for~~ further encoded with computer-readable code for configuring a computer system to identifying a set of services to which the message is addressed.

42. (Currently Amended) The computer readable medium program of claim 3717, ~~comprising computer executable instructions for~~ further encoded with computer-readable code for configuring a computer system to determining ~~determine~~ whether the sender is authorised to access at least one service; and, in dependence on the result of said authorisation determination, sending the converted message to the identified service.

43. (Currently Amended) The computer readable medium program of claim 3717, ~~comprising computer executable instructions for~~ further encoded with computer-readable code for configuring a computer system to searching for data identifying the status of a transaction by reference to a detected transaction identifier.

44. (Previously Presented) A computer system for routing messages to one or more services, comprising:
means for parsing a message received from a sender;
means for parsing including means for converting the message into an internal format, wherein said converting comprises adding an attribute part to a data part of the received message, said attribute part containing data extracted from received message and data indicative of a protocol by which the message was received; and
means for routing the converted message in dependence on the data in the attribute part.

45. (Previously Presented) A computer network comprising at least one computer system connectable to at least one further computer system via a network, the at least one computer system comprising:

a parser for converting a message received from a sender into an internal format, wherein said converting comprises adding an attribute part to a data part of the received message, said attribute part containing data extracted from the received message and data indicative of a protocol by which the message was received; and
a router for routing the converted message in dependence on the data in said attribute part.